

# 50/125 Multimode Fibre to TIA/EIA-492AAAC, ISO/IEC 11801 OM-3 TYPE and IEC 60793-2-10 A1a.2

## Features and Benefits

The following details summarise the main Optical, Geometrical and Physical Characteristics of fibres for the CATV/industrial market, compliant to TIA/EIA-492AAAC, ISO/IEC 11801 OM-3 Type and IEC 60793-2-10 A1a.2. Fibres are manufactured from high grade silica, doped as necessary to achieve the required light guiding properties, designed with a matched-cladding, graded-index profile. The fibre coating is a dual layer structure of ultra-violet cured acrylate resin. The lower modulus inner layer being optimised for both adhesion to the fibre surface and mechanical stripping using the appropriate stripping tools. The outer layer is optimised for abrasion resistance and fibre processing properties.

Optical Properties		Value	Units
Attenuation Coefficient (2F)	850 nm	≤ 3.2	dB/km maximum
	1300 nm	≤ 1.2	dB/km maximum
Attenuation Coefficient (4F,8F,12F)	850 nm	≤ 2.6	dB/km maximum
	1300 nm	≤ 0.8	dB/km maximum
Numerical Aperture		0.20 ± 0.015	-
Minimum Modal Bandwidth	850 nm	1500	MHz.km minimum
	1300 nm	500	MHz.km minimum
Effective Modal Bandwidth	850 nm	2000	MHz.km minimum
Zero-Dispersion Wavelength		≥ 1295 ≤ 1320	nm
Zero-Dispersion Slope	1295-1300 nm	≤ 0.001 ( $\lambda_0$ -1190)	(ps/(nm <sup>2</sup> .km))
	1300 - 1320 nm	≤ 0.11	(ps/(nm <sup>2</sup> .km))

Geometrical Properties		Value	Units
Core Diameter		50 ± 2.5	µm
Reference Surface Diameter		125 ± 1.0	µm
Core to Cladding Concentricity Error		≤ 1.5	µm
Reference Surface Non-Circularity		≤ 1.0	%
Coating Diameter (Coloured)		235 to 255	µm

Physical Properties		Value	Units
Proof Test Level		≥ 1	%

Prysmian Telecom Cables & Systems UK Ltd, Chickenhall Lane, Bishopstoke, Hants SO50 6YU, UK

Technical Enquiries +44 (0) 2380 608760 Fax Number +44 (0) 2380 608769

© Prysmian Telecom Cables & Systems UK Ltd. All Rights Reserved. Issue 01, November 2005.

Sirocco is a registered trade mark of Prysmian Telecom Cables & Systems UK Ltd. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian reserves the right to alter specifications to take account of technical advances and market changes. The products listed in this data sheet are sold under licence from British Telecommunications PLC and are protected by the following patents: EP 0108590, EP 0300647, GB 2205960, EP 0490968, US 4691896, GB 2210472, US 5789701, EP 0287225, EP 0345043, EP 0253636, EP 0363131, EP 0363188, WO 98/12588, EP 0389303, EP 0296860, EP 0157610, EP 0432171, EP 0521710.

**Issue 01, November 2005**  
Ref: SB/01