



Exploration & Production

Protectors

Dual String Protector

SPECIALTY: DUAL STRING PROTECTOR

Protectors are designed to ensure that all control lines and cables are protected for the full length of the production string, thus reducing the risk of damage to cable, control line, or flatpacks. PDT's Protector portfolio includes clamping and cable protection solutions to protect cables from lateral, axial, and rotational loading in downhole applications. In addition to our standard cross-coupling range, PDT designs application specific solutions for demanding situations

APPLICATION

Dual string protectors are used when completions require two production strings. Production tubing strings are typically different sizes.

The centralizer is mounted over the primary production string connection allowing the secondary string to move freely.

STANDARDS & APPROVALS

- All parts comply with NACE Standard MR0175 / ISO 15156

QUALITY & TESTING

- Manufactured in accordance with standard Inspection and Quality Test Plans
- Design Validation Testing
 - Axial, Lateral, Rotational Testing
- Factory Acceptance Testing
 - Visual Inspection
 - Make Up / Fit Test
 - Dimensional Inspection
 - Gap Verification
 - Cable Pull test
 - Drift Verification
 - Torque Test

DESIGN & CONSTRUCTION

- All cast - no welded parts
- One-piece assembly with captive fasteners
- No loose parts
- Interlocking Straps
- Hex or Allen Socket Bolt Option
- Chamfered ends to prevent hang up
- Supports minimum of 100' of downhole cable, control line, and flatpack weight
- Quick and Easy to install
- Reusable
- Custom designs to meet application

Materials

- Carbon Steel
- 316 SS
- 13Cr
- 25Cr
- Super Duplex

Axial Loading

- 30 ton

Lateral Loading

- 30 ton

Rotational Loading

- 3 ton

Common Tubing Sizes

- 2- 3/8" / 2- 7/8" / 3- 1/2" / 4- 1/2" / 5" / 5- 1/2" / 6" / 6- 5/8" / 7"



CONTACT INFO:

downhole@prysmiangroup.com

www.prysmiangroup.com/contact-us