

Oil & Gas - PDT - Prysmian Downhole Technology

Exploration & Production

Protectors

Splice / Gauge Protector

SPECIALTY: SPLICE / GAUGE PROTECTOR

Protectors are designed to ensure that all control lines and cables are protected for the full length of the production string, thus reducing the risk of damage to cable, control line, or flatpacks. PDT's Protector portfolio includes clamping and cable protection solutions to protect cables from lateral, axial, and rotational loading in downhole applications. In addition to our standard cross-coupling range, PDT designs application specific solutions for demanding situations

APPLICATION

Splice/Gauge Protector are designed to suit customers requirements. These protectors are typically used to protect any splicing of downhole cables, control lines, or flatpacks, and provide protection of a downhole gauge or fiber optic termination sub.

STANDARDS & APPROVALS

- All parts comply with NACE Standard MR0175 / ISO 15156

QUALITY & TESTING

- Manufactured in accordance with standard Inspection and Quality Test Plans
- Design Validation Testing Axial, Lateral, Rotational Testing
- Factory Acceptance Testing Visual Inspection
- Make Up / Fit Test Dimensional Inspection Gap Verification Cable Pull test Drift Verification Torque Test

DESIGN & CONSTRUCTION

- All cast no welded parts
- One-piece assembly with captive fasteners
- No loose parts
- Interlocking Straps
- Hex or Allen Socket Bolt Option
- Chamfered ends to prevent hang up
- Supports minimum of 100' of downhole cable, control line, and flatpack weight
- Custom design for customer specific splice of downhole gauge cable or control lines
- Quick and Easy to install
- Reusable
- Custom designs to meet application

Materials

- Carbon Steel
- 316 SS
- 13Cr
- 25Cr
- Super Duplex

Axial Loading

- 30 ton

Lateral Loading - 30 ton

Rotational Loading

Common Tubing Sizes - 2- 3/8" / 2- 7/8" / 3- 1/2" / 4- 1/2" / 5"/ 5- 1/2" / 6" / 6- 5/8" / 7"

