

S-2YC(mS)CY 0.4/2.5

Coaxial SDH-Switch Board Cables acc. to TS 0031/96 part 4



Application

Standards

acc. to TS 0031/96 part 4

Flame resistance

Construction

Inner conductor	copperclad steel wire, bare, diameter 0.4 mm
Insulation	PE 2.45 mm
Outer conductor	copper braid, tinned
Wrapping	PET-foil
Magn. Screen	iron tape, highly permeable
Wrapping	PET-foil
Static screen	copper braid, tinned
Sheath	PVC 4.8 mm white

S-2YC(mS)CY 0.4/2.5

Electrical properties

at 20°C

DC resistance	Inner conductor	≤ 360 Ω/km
Mutual capacitance		68 nF/km
Characteristic impedance		75 Ω ± 2%
Transfer impedance	0.1 MHz	≤ 0.8 mΩ/m
	1 MHz	≤ 0.25 mΩ/m
	10 MHz	≤ 0.12 mΩ/m
	100 MHz	≤ 1.2 mΩ/m
Test voltage	Inner/Outer conductor	2 kV _{rms}
Insulation resistance		≥ 10 GΩ*km

Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
1	≤ 2.0	40-300	≥ 23
10	≤ 5.5		
30	≤ 9.5		
100	≤ 18.0		
300	≤ 32.0		
600	≤ 47.0		

Technical data

Product code	Designation	Type	Outer diameter mm	Weight kg/km	Standard delivery length m	Drum size KTG/ring	Gross weight kg	Copper content	Tensile force N
CS2703400	S-2YC(mS)CY	1 x 0.4/2.5 Staku	4.8	41	1000	071	67	22.0	135
					250	ring	10.5		
CS2703402	S-2YC(mS)CY	1 x 0.4/2.5 Staku	4.8	41	250	ring	10.5	22.0	135

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.