


# Digital Sound 10er Modulation cable

## Audio cable AES/EBU



### Application

For analogue and digital audio transmission

Not for fixed installation in construction works

### Construction

Conductor	Stranded copper wires, bare, diameter 0.42 mm
Insulation	Foam-Skin- PE diameter 1.0 mm
Pair stranding	Two cores twisted to the pair
Pair screen	Spiraled copper wires, tinned, diameter 2,2mm
Pair identification	a-core: blue, b-core: white
Pair Insulation	PBT, diameter 2,5mm
Pair colors and identification	Gray RAL 7001 with number printing
Wrapping	Polyester web
Outer screen	CU-braid tined, no drain wire
Outer wrapping	Polyester web
Sheath	DMC FLEX PUR, gray RAL 7016, diameter 10,5 mm
Marking	<b>DRAKA</b> – DIGITAL SOUND 10er Mod. + batch number + meter marking

### Mechanical properties

Bending radius	without load	10 x D ( D= outer diameter)
	with load	15 x D ( D= outer diameter)
Temperature range	fixed operation	- 30° C to + 70° C
	mobile use	- 5° C to + 60° C

## Digital Sound 10er Modulation cable

### Electrical properties

at 20°C

Loop resistance		288 Ω/km
Insulation resistance		1GΩ/KM
Capacity	core/core	< 70 pF/m
	core/screen	< 230pF/m
Characteristic impedance		110Ω
Relative Velocity ratio		78 %
Insulation resistance	core/core	250V
	core/screen	1000V
Transfer impedance	0 - 10MHz	10mΩ/m

### Electrical data (nominal)

at 20°C

Attenuation (dB/100m)		Near end crosstalk (dB)	
Frequency (MHz)		Neighbourised pairs	Unneighbourised pairs
0,015	0,6	> 100	> 100
1,0	2,3		
4,0	6,0		
10,0	10,9		
20,0	17,8		

### Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size *PWD	Copper content	Tensile Force N	Storage
1016552 CT2660700	Digital Sound 10er Mod.	141	1000	760/360/5 80	100	550	Inside

\*PWD (Plywood drum)

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2009, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.